



SN 2 (SERIE 25) SDR=51

DIÁMETRO NOMINAL Dn (mm)	DIÁMETRO EXTERIOR De (mm)	ESPESOR e (mm)	DIÁMETRO INTERIOR Di (mm)	PESO APROX. (Kg)	LONGITUD TOTAL Lt (m)	LONGITUD ÚTIL Lu (m)
160,0	160,0	3,2	153,6	13,900	6,0	5,82
200,0	200,0	3,9	192,2	21,10	6,0	5,80
250,0	250,0	4,9	240,2	33,00	6,0	5,76
315,0	315,0	6,2	302,6	52,80	6,0	5,74
355,0	355,0	7,0	341,0	67,00	6,0	5,72
400,0	400,0	7,9	384,2	86,00	6,0	5,70

SN 4 (SERIE 20) SDR=41

DIÁMETRO NOMINAL Dn (mm)	DIÁMETRO EXTERIOR De (mm)	ESPESOR e (mm)	DIÁMETRO INTERIOR Di (mm)	PESO APROX. (Kg)	LONGITUD TOTAL Lt (m)	LONGITUD ÚTIL Lu (m)
110,0	110,0	3,2	103,6	9,80	6,0	5,85
160,0	160,0	4,0	152,0	17,20	6,0	5,82
200,0	200,0	4,9	190,2	26,50	6,0	5,80
250,0	250,0	6,2	237,6	41,70	6,0	5,76
315,0	315,0	7,7	299,6	65,30	6,0	5,74
355,0	355,0	8,7	337,6	83,00	6,0	5,72
400,0	400,0	9,8	380,4	105,60	6,0	5,70

SN 8 (SERIE 16,7) SDR=34

DIÁMETRO NOMINAL Dn (mm)	DIÁMETRO EXTERIOR De (mm)	ESPESOR e (mm)	DIÁMETRO INTERIOR Di (mm)	PESO APROX. (Kg)	LONGITUD TOTAL Lt (m)	LONGITUD ÚTIL Lu (m)
110,0	110,0	3,2	103,6	9,80	6,0	5,85
160,0	160,0	4,7	150,6	20,00	6,0	5,82
200,0	200,0	5,9	188,2	31,30	6,0	5,80
250,0	250,0	7,3	235,4	48,70	6,0	5,76
315,0	315,0	9,2	296,6	77,00	6,0	5,74
355,0	355,0	10,4	334,2	98,40	6,0	5,72
400,0	400,0	11,7	376,6	124,40	6,0	5,70

NOTAS:

- ▶ Normas de Fabricación: NTP ISO 4435
- ▶ Gama de diámetros: De 110 mm. a 400 mm.
- ▶ Sistema de Empalme: Unión Flexible (UF)
- ▶ Color: Anaranjado Marrón (Ocre)
- ▶ Campo de Aplicación: Recolección de aguas residuales y pluviales, drenaje.

ISO 9001
ISO 14001
OHSAS 18001

BUREAU VERITAS
Certification



Compre al Perú